



Wax Powders and Dispersions for Seed Coatings

Micro Powders offers a range of products that are commercially proven to enhance the performance of seed coatings. Our dry wax powders, dispersions and emulsions can improve a number of properties, including:

- Minimized seed blocking with fewer doubles or skips
- Enhanced surface lubricity for improved seed flow during planting
- Improved seed durability and abrasion resistance, with less dusting in seed processing facilities and in the field
- Enhanced seed appearance

Some of our most popular products for seed coatings include:

| Product: | 40CFR 180 compliance* | | | Chemistry: |
|---|-----------------------|------|-----|--------------------------------|
| | 910 | 950e | 960 | |
| AquaMatte 31 AquaMatte 22 Microspersion 22AQ-50 | | | √ | Oxidized polyethylene |
| MicroKlear 418 | | √ | | Carnauba wax |
| MicroKlear 295 Microspersion 295-45 | √ | √ | | Carnauba wax/polyethylene |
| MicroKlear 709 | √ | √ | √ | Carnauba wax/polyethylene/PTFE |
| AquaKlean 418 | √ | √ | | Carnauba wax emulsion |

In addition to the Microspersion products listed above, we can provide any of the other dry wax products in an aqueous Microspersion form with 40CFR Part 180 compliance.

Please contact us for further information and samples.

- *40CFR 180.910 Inert ingredients used pre- and post-harvest; exemptions from the requirement of a tolerance
- *40CFR 180.950(e) Tolerance exemptions for minimal risk active and inert ingredients; *Specific chemical substances*
- *40CFR 180.960 Polymers; exemptions from the requirement of a tolerance



Rev.03/15

Micro Powders, Inc.

580 White Plains Road, Tarrytown, NY 10591
TEL 914.793.4058 FAX 914.472.7098
Email: mpi@micropowders.com

The information contained herein is to the best of our knowledge true and correct and any suggestions are made without guarantee, express or implied, since conditions of use are beyond our control. Micro Powders, Inc. disclaims any liability incurred in connection with the use of any data or suggestions. Nothing contained herein shall be construed as a recommendation to infringe on any existing patents covering any material or its use.

Certified to ISO 9001